

DUNA - SELEÇÃO DE CABOS ELÉTRICOS 220V / 380V

Modelo	Corrente média	Bitola do cabo - até 50m	Bitola do cabo - até 100m
Duna 20M	5,5 A	2,5 mm	4,0 mm
Duna 50M	11,5 A	5,5 mm	4,0 mm
Duna 65M	15,0 A	4,0 mm	6,0 mm
Duna 65T (220V)	10,5 A	2,5 mm	4,0 mm
Duna 65T (380V)	8,0 A	2,5 mm	4,0 mm
Duna 80M	25,0 A	6,0 mm	10,0 mm
Duna 80T (220V)	11,5 A	2,5 mm	4,0 mm
Duna 80T (380V)	9,0 A	2,5 mm	4,0 mm
Duna 100M	24,0 A	6,0 mm	10,0 mm
Duna 100T (220V)	16,5 A	4,0 mm	6,0 mm
Duna 100T (380V)	12,0 A	2,5 mm	4,0 mm
Duna 120M	27,0 A	6,0 mm	10,0 mm
Duna 120T (220V)	18,0 A	4,0 mm	6,0 mm
Duna 120T (380V)	13,0 A	2,5 mm	4,0 mm
Duna 150T (220V)	24,0 A	6,0 mm	10,0 mm
Duna 150T (380V)	17,0 A	4,0 mm	6,0 mm
Duna 180T (220V)	30,0 A	6,0 mm	10,0 mm
Duna 180T (380V)	20,0 A	4,0 mm	6,0 mm